



Barcode Label Printing Scale LP-AE



Function & Features:

Big storage capacity: 10000 PLUs data storage capacity, plus extra storage option.

Powerful data processing: 80 PLU Hot-Key, Programmed and printed in PC.

Various special selling modes: Discount in percentage or coupon; Additional charge in percentage or other extra charge; Change price anytime etc.

Different type of selling: Weighing, Default price, Default price and weight selling.

Powerful network communication: program setting, multiple-machine networking, back-office management via either RS-232 or TCP/IP.

Easy programming: PLUs database, Label code format, system parameters, Hot-Keys, 8-letter strings, 255 explanations to be edited in PC or directly in scale.

Convenient label code formatting: label code and printing setting to be customized.

Key Parameters

ITEM	PARAMETERS
Precision	1/3000
Weight Scope	0-6Kg-15Kg or 0-15-30Kg
Weight Resolution	2/5g or 5/10g
Storage Capacity	10,000 PLUs
Display	Double sides displays with the pole - LCD: 128x25 dots(21 lettersx2 lines, White backlight) - LED Digital Tube: Red, 5/6 digits(Weight/Unit Price)
Keyboard	112 keys (80x2=160 PLUs Hotkeys, 32 Function keys)
Printing Type	Thermal Printing, Printing Speed: >50mm/s, Paper Width: 58mm, Printing Width: 56mm, Recommended Label Size: 58mm(W)x37mm(L)
Paper Roll Outer Diameter	80mm (Max)
Paper Roll Internal Diameter	42mm (Min)
Ports (Standard)	1xRS232, 1xRJ45 Ethernet
Ports (Optional)	None
Power Input	AC100-120V or AC200-240V 50/60Hz, 0.5A
Battery Inside	None
Dimension(mm)	420 (W)x480 (D)x190 (H) (the height is 510mm including display pole)
Net Weight	About 10Kg
Work Environment	Temperature: -10°C~40°C; Humidity: 20%~85% RH
Storage Environment	Temperature: -20°C~50°C; Humidity: 10%~95% RH