

Power Belt Check Weigher MCS-E



Full Range of Checkweighers

Dynamic checkweigher series products include medium and low-speed checkweighers suitable for vertical packaging machines, high-speed checkweighers suitable for pharmaceutical and food quality inspection, and large-scale checkweighers suitable for packaging and logistics industries. Heavy technical performance is very good. global series of products are committed to assisting the needs of online production weighing, quality inspection, etc. in hardware, food, pharmaceutical, daily necessities, logistics and other industries, and provide one or more solutions. In addition, also provides integrated solutions, through the combination of dynamic checkweighers and other product inspection technologies (such as: metal detection, X-ray inspection and visual inspection), so as to meet the more comprehensive needs of customers and provide more complete solutions .

Total solution

Comprehensive solution of dynamic checkweigher and metal detector system Comprehensive solutions for dynamic checkweighers and packaging machines Comprehensive solutions for dynamic checkweighers and labelling machines (jet printers) Supported by distributors and ancillary suppliers around the world

Diverse product options

Up to 20 standard dynamic checkweighers and additional optional devices Provide a variety of ranges and materials (eg: carbon steel spray, aluminum alloy, stainless steel) to meet different needs and environments Provides a variety of data communication standards (Example: Ethernet, RS485 and RS232 technology), which can realize seamless connection with data network suppliers around the world Remote maintenance technology, support remote maintenance and remote upgrade

Support Industrial cloud and IOT integration mechanism

Feature:

Suitable for re-inspection of sealing and packing lines Various sizes can be customized, product length 200-2000mm Fits light weight, uneven bottom surface Soft package products Reliable accuracy Flexible configuration for standard weighing applications Rugged construction with heavy load capacity Optional standard RS232\RS485\TCP interface Weighing range: 2 kg - 50 kg Accuracy: \pm 20 g ~ 50 g Work efficiency: \leq 15 pieces/min Touch screen size: 7 inches

Production Size:

	Type1	Type2	Туре3
А	800		
В	600	800	1000



