



1mg Halogen Lamp Moisture Analyzer MS



MS Series				
Model	100MS	100MS(plus)	200MS	200MS(plus)
Range (g)	110g		210g	
Readability(g)	0.001g		0.001g	
Operating Temp	5°C-35°C			
Pan Size	100mm			
Heat Source	Halogen Lamp			
Temp.Sensor	PT 100			
Temp. Range	40°C-230°C			
Temp.Step	1°C			
Moisture Range	0.00%-100.00%			
Moisture Readability	0.01%			
Dry Residual Range	100.00%-0.00%			
Dry Residual Readability	0.01%			
ATRO	100%-999%			
ATRO	0%-999%			
Temp Setting	40°C-230°C By 1°C Step			
Time Setting	1-99min by 10s			
Number Of Storage	20			
Number Of History	20			
Heater	220V±15% 50HZ/ 110V±15%60HZ 400W			
Balance	Input:220V 50HZ/110V 60HZ Output:9V			
Machine	Input: 220V 50HZ/110V 60HZ Output:24V (Dual-drive)			

Host Dimension	215X195X415mm			
Indicator Dimension	200X75X135mm			
Operation Height	275mm			
The Chamber Height	35mm			
Display	7inch touch panel			
Interface	RS232/RJ45/USB			
Communication Mode	Cable	Wireless	Cable	Wireless
Rechargeable Battery	No	10,000mAh	No	10,000mAh
Calibration	External Calibration			

MS Series Moisture Analyzer Functions:

1. Automatic open the heating chamber. Keep the weighing and test more stable.
2. 7 inch HD display, moisture analysis curve, moisture content /dry weight /dry weight direct display;
3. 40-230°C limit heating temperature;
4. The test height 35cm;
5. The window can look the test sample;
6. 20 groups of setting address;
7. 20 groups of history can check and print;
8. Max weight can choose 200g;
9. HBM weighing sensor;
10. 4 sets of stainless steel;
11. The special material case suit for high temperature test;
12. Appearance and structure to obtain a number of patents;
13. Easy cleaning for open test chamber;
14. Easy fix and repair design;
15. Intelligent system can protect operation not crush by machine;
16. New system update easily.



Intelligent Moisture Analyzer



Intelligent Moisture Analyzer

