



Halogen Moisture Analyzer MW-T



MW-T Series Moisture Analyzer	
Mode	MW-T
Range(g)	110g
Readability(g)	0.001g
Operating Temp	5°C-35°C
Pan Size	Ø 90mm
Heat Source	Halogen Lamp
Temp.Sensor	PT 100
Temp.Range	40°C-199°C
Temp.Step	1°C
Moisture Range	0.00%-100.00%
Moisture Readability	0.01%
Dry Residual Range	100.00%-0.00%
Dry Residual Readability	0.01%
Temp Setting	40°C-199°C By 1°C Step
Time Setting	1-99min by 10s
Number Of Storage	20
Number Of History	20
Heater	220V±15%50HZ 400W
Balance	Input:220V 50HZ Output:9V
Host Dimension	360X490X350mm
The Chamber Height	22mm

Display	5 inch touch panel
Calibration	External Calibration
Interface	RS232

Use halogen moisture analyzer should attention:

- 1.halogen moisture analyzer is used to measure the moisture content in the sample, used for any other purpose are likely to cause harm and personal damage the instrument.
2. Please read the instructions carefully before you use it, do not use it under the environment condition which not meet the requirements.
3. halogen rapid moisture analyzer only suit for professional operate.
4. halogen rapid moisture analyzer for power for the three plug with earthing socket, banned disconnect apparatus grounding or use without a good grounding power supply.
5. Instrument around should ensure that there is enough space, so as to avoid heat accumulation and heat.
- 6.Please do not put flammable and explosive goods around the instrument.
7. After the test, the heating unit and the container is still very hot, so please do not touch it.
8. Toxic substances testing should be under ventilation environment