



80mm Barcode Label Printer POS-360B



Feature:

152mm/s high-speed printing

Auto-check paper function

Open cover out of paper alarm function

Built-in power supply saves office space

Large memory DRAM: 4M

Large FLASH: 4M

Support PDF417, QR_CODE, DATAMATRIX three-dimensional barcode printing

Specification:

Print	printing method	Direct line thermal
	Resolution	203 DPI
	print width	76mm
	Printing speed	152mm/s
RAM	memory	DRAM: 4M FLASH: 4M
Communication Interface	Communication Interface	USB interface
Print head	print head position detection	Micro Switch
	paper presence detection	photoelectric sensor
Barcode Character	barcode	CODE128, EAN128, ITF, CODE39, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR,
Graphics		

		POSTNET, UPC-A, UPCA+2, UPCA+5, UPC-E, UPCE+2, UPC-E+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14
	character set	Common single-byte fonts: FONT 0 to FONT 8
	Character enlargement/rotation:	Both horizontal and vertical can be enlarged 1-10 times, and rotated to print ((0°, 90°, 180°, 270°)
	graphics	Monochrome PCX, BMP and other image files can be downloaded to FLASH, DRAM
medium	paper type	Thermal roll paper, self-adhesive paper, etc
	Media width	20mm ~ 82mm
	Outside diameter of paper roll	≥80mm
	Inner diameter of paper roll	≤25mm
	paper output	tear off
Power Supply	Input	AC 100-240V, 50~60Hz
Physical Properties	Net Weight	1.44kgs
	Production Size	212.4(D) x 143(W) x 145.5(H)mm
Environmental requirements	working environment	5 ~ 45°C, 20 - 80%RH (non-condensing)
	storage environment	-40 ~ 55°C, ≤93%RH (40°C)