

## 58mm Thermal Ticket Receipt Printer POS-58A



### Feature:

- Support dual module, dual software printing
- Integrated power supply and body, saving space
- USB/USB+Blue tooth interface
- Simplified and multiple international languages supported
- Support Windows 7, Windows 8, Linux system driver
- Support download Logo trademark printing

### Specification:

Printing	printing method	direct line thermal
	print width	48mm
	Column capacity	384 dots/line
	Printing speed	90mm/s
	Interface Type	USB+Blue tooth
	printer paper	57.5±0.5mm×φ60mm
	Line spacing	3.75mm (line spacing can be adjusted with commands)
	number of columns	58mm paper: 58mm paper: Font A - 32 columns / Font B - 42 columns / Simplified, Traditional - 16 columns
	character size	ANK characters, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots)

		Simplified/Traditional: 3.0×3.0mm (24×24 dots)
Barcode Characters	extended character list	PC347 (Standard Europe, Katakana, PC850 (Multilingual) PC860 (Portuguese) PC863 (Canadian-French) PC865 (Nordic) West Europe, Greek, Hebrew, East Europe, Iran WPC1252, PC866 (Cyrillic#2) , PC852 (Latin2) PC858, IranII, Latvian, Arabic, PT151 (1251)
	Barcode Type	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128
Buffer	Input Buffer	32k bytes
	NV Flash	64k bytes
Power Supply	Power Adapter	Input: AC 110V/220V, 50~60Hz
	Power Supply	Output: DC 12V/2.6A
	Cash drawer output	DC 12V/1A
Physical Properties	Net weight	0.56KGS
	Production Size	180×130×108mm
Environmental Requirements	Working Environment	Temperature: 0~45℃, Humidity: 10~80%
	Storage Environment	Temperature: -10~60℃, Humidity: 10~90% (non-condensing)
Life	Reliability	50km