

80mm Bluetooth Thermal Ticket Receipt Printer POS-80B



Feature:

POS-80B is an economic model with USB or Lan port, with auto cutter.

Column capacity : 576 dots/line 512 dots/line

Printing speed : 160mm/s

Interface : USB / Lan

Printing paper : 79.5±0.5mm×φ80mm

Line spacing : 3.75mm (Adjustable by commands)

Specification:

Printing	printing method	direct thermal
	Printing speed	160mm/s
	Interface Type	USB /Lan
	Paper width	72mm
	Printing paper	79.5±0.5mm×φ80mm
	Print command	Compatible with ESC/POS

	Column capacity :	576 dots/line 512 dots/line
	Line space	3.75mm (Adjustable by commands)
	Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/Chinese, traditional Chinese - 21 columns or 24 columns
	Character size:	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B:1.1×2.1mm (9×17 dots) Chinese, traditional Chinese:3.0×3.0mm (24×24 dots)
Code page:	extended character list	PC347 (Standard Europe), Katakana , PC850(Multilingual), PC860 (Portuguese) PC863 (Canadian-French), PC865 (Nordic), West Europe ,Greek , Hebrew , East Europe Iran , WPC1252, PC866(Cyrillic#2), PC852 (Latin2), PC858, Iranll, Latvian, Arabic , PT151 (1251)
Barcode Characters	Barcode Type	UPC-A/UPC-E/JAN13(EAN13)/JAN (EAN8/CODABAR/CODE39/CODE128
Cutter	automatic cutter	Partial
Buffer	Input Buffer	64k bytes
	NV Flash	256k bytes
Power Supply	Power adaptor	Input: AC 110V/220V, 50~60Hz
	Power Supply	Output: DC 24V/2.5A
	Cash drawer output	DC 24V/1A
Physical Properties	Net weight	0.98KGS
	Production Size	184.5×145×153mm (D×W×H)
Environmental	Working Environment	Temperature: 0~45℃, Humidity: 10~80%
Requirements	Storage Environment	Temperature: -10~60℃, Humidity: 10~80%
Reliability:	Cutter life	1 million cuts
	print head life	50km