



80mm Bluetooth 203dpi Thermal Ticket Receipt Printer POS-80I



Features





Feature:

- Bluetooth can be options
- Compatible ESC/POS programming language
- open access for easy paper loading
- Media cover open sensor
- Change IP through Web or Serial port

Specification:

Printing	printing method	direct thermal
	Resolution	203dpi
	Printing speed	200mm/s
	Interface Type	USB-Serial/Lan /USB+Bluetooth
	Paper width	80mm
	Paper roll diameter	≤80mm
	Paper thickness	0.06-0.08mm
	Print command	Compatible with ESC/POS
	Column capacity :	576 dots/line 512 dots/line (80mm)
	Line space	3.75mm (changeable using commands)

	Character size:	ANK, Font A;12*24dots Font B:9*17 dots Simplified/traditional Chinese 24*24dots
Code page:	extended character list	PC347 (Standard Europe), Katakana , PC850(Multilingual), PC860 (Portuguese) PC863 (Canadian-French), PC865 (Nordic), West Europe ,Greek , Hebrew , East Europe Iran , WPC1252, PC866(Cyrillic#2), PC852 (Latin2), PC858, Iranll, Latvian, Arabic , PT151 (1251)
Barcode Characters	Barcode Type	UPC-A/UPC-E/JAN13(EAN13)/JAN (EAN8/CODABAR/CODE39/CODE128
Cutter	automatic cutter	Full/Partial (optional)
Buffer	Input Buffer	64k bytes
	NV Flash	256k bytes
Power Supply	Power Supply	DC 24V/2.5A
	Cash Drawer control	DC 24V/1A
Physical Properties	Net weight	1.1KGS
	Production Size	195x140x142.5mm (DxWxH)
Environmental Requirements	Working Environment	Temperature: 0~45°C, Humidity: 10~80%
	Storage Environment	Temperature: -10~45°C, Humidity: 10~80%
Drivers:		Win 9*Win ME/Win 2000/ Win 2003/Win NT/ Win XP/Win Vista/ Win 7/ Win 8 / Win10/Linux/OPOS
Reliability:	Cutter life	1 million cuts
	print head life	100km