

15" PC Based Terminal Dual Touch Pos System POS-T901



Classical appearance design with advanced surface structure handling; Modular design introduces excellent user experience and service efficiency; Availability of plenty of peripherals provides users more function choices; Different levels of hardware configurations satisfy different user demands; Metal back housing helps the heat sinking to provide more system stability. User friendly design of cable cover provides a very neat outer appearance.

Features:

Aluminum housing design.

Fan-less design.

Customized mainboard with few cable connections. The inside is very neat.

The HDD/SSD is pluggable from outside.

Rotatable and inseparable cable cover.

Easy to add customer display or secondary monitor.

Peripheral connection cables could easily go through the base and be fixed well.

Pluggable Dallas Lock / MSR modules without cable connection.

Specification:

CPU	Intel Baytrail-D,Celeron J1900,2.0GHz up to 2.41GHz ,TDP 10W
Graphics	Intel HD Graphics
Graphic Output	VGA,LVDS,EDP
Display	15" TFT LCD, 1024 x 768;
Viewing Angle	45 degree adjustable
Touch Solution	15" Capacitive touch panel;
RAM	DDR3L 1333/1600MHz, 4GB as standard, optional up to 8GB
Storage	64GB SSD as standard, optional up to 256GB, 1 x SATA, 1 x M-SATA
Audio	Realtek ALC 662HD (on board)
LAN	Realtek RTL8106E-CG, (on board)
Extended Slots	1 x MINI-PCIE (for 4G/WIFI), 1 x Micro-SIM (on board)

I/O Ports	1 x DC24V_IN 1 x DC12V_OUT 1 x RJ11 for cash box 3 x RJ48 for RS232 4 x USB2.0 + 1 x USB2.0 1 x RJ45 for LAN 1 x VGA 1 x LINE-OUT
O.S. Compliant	Windows 8, Windows 10, Linux (not included)
Input Power	ø2.5 x DC12V
Power Supply	100 ~ 240V / 47 ~ 63Hz
Work Environment	-10 ~ 60 degrees, 0% ~ 95%