

New Arrival 4 20Ma Pressure Transmitter for oil PS-1000



Product Features:

Easy installation and strong versatility

Efficient lightning protection

Anti-surge and reverse polarity protection

High elasticity, wear resistance

Excellent shock, overload, & vibration resistance

Advanced temperature digital compensation function

Applications:

Industrial process and control

Automated detection

Hydraulic and full-motion control

Water treatment system

Industrial machinery manufacturing

Pumping stations

Features

Easy installation and strong versatility

Efficient lightning protection, strong anti-radio frequency and electromagnetic interference protection Anti-surge and reverse polarity protection

High elasticity, wear resistance, impact resistance, vibration resistance and corrosion resistance Advanced temperature digital compensation function

Technical indicators

Measuring mediu	water, gas, oil, Hydraulic
Range	5, 7, 10, 15, 20, 25, 32, 50Bar (gauge pressure)
Output signal	4~20mA
Precision	±1%FS
Supply voltage	9~30V DC
Medium temperature	-40° ℃~+85°℃
Storage temperature	-40℃~+125℃

Temperature compensation	-10℃~+70℃
Long-term stability	≤±0.2%FS/year
Allow overload	200%FS
Breaking pressure	300%FS(≤250bar)
Shock (11mS)	100g
Zero temperature drift	±0.02%FS/℃
Full scale temperature drift	±0.02%FS/°C
Pressure port	M20*1.5, G1/4; optional NPT1/4, G1/2
Electrical connections	Large Hessmann connector,
	others can be customized