



## Thermal Printing Cash Register Scales TPS-B



### Function

Support multi-language printing, including Chinese, English, Arabic, Persian, Spanish, Vietnamese, etc.  
1,000 PLUs storage capacity.

Has 70(35x2) Hotkeys, easy for calling out the goods for sale.

Using special PC software, setup and print the keyboard hotkeys distribution, inserting the paper of hotkeys distribution into the keyboard hotkeys area below, intuitive operation fast.

Daily report query and print functions.

A bill may be accumulated continuously weighing 50 goods.

Re-print the last receipt.

Support the weighting sales and quantity sales.

Support Change, Tare, Zero, Add, Back space, Cancel, Print, Open cash drawer, and other Functions.

Setting the machine's date and time and date.

Setting receipt head and tail titles.

Connect with U-disk for adding reports storage, stock each receipt detailed content and daily report.

Transfer the receipt head and tail titles by U-disk or RS232 port, and can manage all the data by the PC software which in the CD.

**Key Parameters:**

ITEM	PARAMETERS
Precision	1/3000
Weight Scope	0-6Kg-15Kg or 0-15-30Kg
Weight Resolution	2/5g or 5/10g
Storage Capacity	1,000 PLUs
Display	Double sides displays with the pole - LED Digital Tube: Red, 5/5/6 digits(Weight/Unit Price/Total Price)
Keyboard	60 keys (35×2=60 PLUs Hotkeys, 25 Function keys)
Printing Type	Thermal Printing, Printing Speed: >50mm/s, Paper Width: 57.5±0.5mm, Printing Width: 48mm
Paper Roll Diameter	50mm (Max)
Ports (Standard)	1×RS232, 1×RJ11 for Cash Drawer, 1×USB (U-Disk)
Ports (Optional)	None
Power Adapter	Input: AC100-240V 50/60Hz; Output: DC7.5V/3A
Battery Inside	6V/4A
Dimension(mm)	367 (W)×410 (D)×125 (H) (the height is 465mm including display pole)
Net Weight	About 5.2Kg
Work Environment	Temperature: -10°C~40°C; Humidity: 20%~85% RH
Storage Environment	Temperature: -20°C~50°C; Humidity: 10%~95% RH